

KAMERY DOMERA® INFORMACJE

ŁATWE POŁĄCZENIE Z **PONAD 90%** WSZYSTKICH TYPOWYCH APLIKACJI WIDEO



RDF6800DN



RDF6400DN



RDF5140DN

Ilość pikseli czujnika	8 Megapixel		4 Megapixel		5 Megapixel	
Obiektyw	F1.3 / 4.5–9.7 mm	F1.8 / 12–40 mm	F1.3 / 4.5–9.7 mm	F1.8 / 12–40 mm	F1.4 / 3–10 mm	F1.8 / 12–40 mm
Kąt widzenia poziomy	110°–47°	35.2°–12.1°	111.2°–47.5°	36.1°–12.4°	111.0°–31.9°	23.8°–8.3°
Maksymalna rozdzielczość	3840 x 2160		2688 x 1520		2592 x 1944	
Wrażliwość na światło	< 0.05 lux (AGC ON)		< 0.0005 lux (AGC ON)		< 0.03 lux (AGC ON)	
VCA Analityka	✓		✓		✓	
AI Analityka	✓		✓		–	
Regulacja osi z napędem silnikowym	✓		✓		✓	
Tryb korytarzowy	✓		✓		✓	
Światło IR/białe	360°✓ 1 / 360° ¹		360°✓ 1 / 360° ¹		360°✓ ¹ / 360°✓ ¹	
ONVIF	M / S / T		M / S / T		S / T	
Audio I/O	✓ ¹		✓ ¹		–	



RDF5120DN



RDF5140DN (E)



RDF5120DN (E)



SDF6800DN

2 Megapixel		5 Megapixel		2 Megapixel		8 Megapixel
F1.4 / 3–10 mm	F1.8 / 12–40 mm	F1.4 / 3–10 mm	F1.8 / 12–40 mm	F1.4 / 3–10 mm	F1.8 / 12–40 mm	F2.8 / 1.6 mm Fisheye
111.0°–31.9°	23.8°–8.3°	111.0°–31.9°	23.8°–8.3°	111.0°–31.9°	23.8°–8.3°	360°
1920 x 1080		2592 x 1944		1920 x 1080		2880 x 2880
< 0.03 lux (AGC ON)		< 0.03 lux (AGC ON)		< 0.03 lux (AGC ON)		< 0.05 lux (AGC ON)
✓		✓		✓		✓
–		–		–		✓
✓		✓ ₂		✓ ₂		–
✓		–		–		–
360°✓ ¹ / 360°✓ ¹		180°✓ 1 / –		180°✓ 1 / –		360°✓ 1 / 360° ⁰¹
S / T		S		S		M / S / T
–		–		–		✓ ¹